VITATION TO BID	or 1000		
TATE OF LOUISIANA		APR 27, 2006	04:00 PM
VISION OF ADMINISTRATION			
FFICE OF STATE PURCHASING		PURCHASING AGENCY N FAX SOLI	0.: 107001 CITATION
VENDOR NO. :			to (225) 342-8688
SOLICITATION: 2207261 FILE NO.: M10165B			e indicated.
OPENING DATE: 04/27/06		SEE NO. 8 BELOW.	
	_		04:00 PM
			7/06 M10165B
		OFFICE OF STATE PURC OFFICE OF STATE PURC POST OFFICE BOX 9409 BATON ROUGE, LA 7080	HASING HASING 5 4-9095
	_	BUYER PHONE	: 04/20/06 : 419954 FOLD HERE>
		AGENCY REQ. NO. ISIS REQ. NO. VENDOR PHONE FISCAL YEAR CLASS/SUBCLASS SCHEDULED BEGIN DATE SCHEDULED END DATE T-NUMBER	: 11279/419 : 1287578 : 06 : 07059 : 00/00/00
PLEASE REMOVE FROM THIS COMMODITY CODE. DELIVERY WILL BE MADE IN THIS NUMBER OF DAYS AFTER REGISTED. CASH DISCOUNT FOR PROMPT PAYMENT IF MADE WITHIN THE LESS THAN 30 DAYS OR LESS THAN 1% WILL BE ACCEPTED, BLUEST THAN 10 DETERMINING AWARDS. ON INDEFINITE QUANTITY TERM CONTROL BUT WILL NOT BE CONSIDERED IN DETERMINING AWARDS. BID BOND ATTACHED. CERTIFIED CHECK ATTASES. BID REFERENCE NUMBER. (THIS NUMBER WILL APPEAR ON REGISTED.)	RIRTY (30) DAYS. CASH (IT WILL NOT BE CONSID RACTS, CASH DISCOUN CHED,OTH	ERED IN TS WILL BE ACCEPTED AND TAKEN ER, IF REQUIRED.	
		1	
 READ THE ENTIRE BID, INCLUDING ALL TERMS AND CONDITIONS AND S ALL BID PRICES MUST BE TYPED OR WRITTEN IN INK. ANY CORRECTION INITIALED BY THE BIDDER. THIS BID IS TO BE MANUALLY SIGNED IN INK. BID PRICES SHALL INCLUDE DELIVERY OF ALL ITEMS F.O.B. DESTINAT OR "C.O.D" REQUIREMENTS MAY BE REJECTED. PAYMENT IS TO BE M 	ONS, ERASURES OR OTH	PROVIDED. BIDS CONTAINING "PAYM	FOLD HERE>
INVOICE OR DELIVERY, WHICHEVER IS LATER. 5. AMOUNT OF BID BOND REQUIRED:			
6. AMOUNT OF PERFORMANCE BOND, IF REQUIRED	OR	0% OF BID.	
8. TO ASSURE CONSIDERATION OF YOUR BID, ALL BIDS AND ADDENDAS THE BID OPENING DATE AND THE BID NUMBER, OR SUBMITTED IN THE 9. BIDS SUBMITTED ARE SUBJECT TO PROVISIONS OF THE LAWS OF THE PURCHASING RULES AND REGULATIONS; EXECUTIVE ORDERS; STANG IN THIS SOLICITATION. 10. IMPORTANT: BY SIGNING THE BID, THE BIDDER CERTIFIES COMPLIAN	SPECIAL ENVELOPE IF ESTATE OF LOUISIANA I DARD TERMS AND CONE	FURNISHED FOR THAT PURPOSE. NCLUDING BUT NOT LIMITED TO L.R.S ITIONS; SPECIAL CONDITIONS; AND S	s. 39:1551-1736; SPECIFICATIONS LISTED
SPECIFICATIONS, AND FURTHER CERTIFIES THAT THIS BID IS MADE W BY A PERSON AUTHORIZED TO BIND THE VENDOR (SEE NO.30). ALL B			
VENDOR PHONE NUMBER:	TITLE		DATE
FAX NUMBER:			
SIGNATURE OF AUTHORIZED BIDDER - SEE NO. 30, PAGI (MUST BE SIGNED)		E OF BIDDER ED OR PRINTED)	

STANDARD TERMS & CONDITIONS	INVITATION TO BID	
NUMBER : 2207261 OPEN DATE: 04/27/06 T-NUMBER :	BIDDER:	PAGE 2

11 ADDRESS ALL INQUIRIES AND CORRESPONDENCE TO THE BUYER AT THE PHONE AND ADDRESS SHOWN ABOVE.

12. CONFERENCE:

NA

NA

NA

13. BID FORMS.

ALL WRITTEN BIDS, UNLESS OTHERWISE PROVIDED FOR, MUST BE SUBMITTED ON, AND IN ACCORDANCE WITH, FORMS PROVIDED, PROPERLY SIGNED (SEE NO. 30). BIDS SUBMITTED IN THE FOLLOWING MANNER WILL NOT BE ACCEPTED:

- A. BID CONTAINS NO SIGNATURE INDICATING INTENT TO BE BOUND;
- B. BID FILLED OUT IN PENCIL; AND
- C. BID NOT SUBMITTED ON THE STATE'S STANDARD FORMS.

BIDS MUST BE RECEIVED AT THE ADDRESS SPECIFIED IN THE SOLICITATION PRIOR TO BID OPENING TIME IN ORDER TO BE CONSIDERED.
TELEGRAPHIC AND FAX ALTERATIONS TO BIDS RECEIVED BEFORE BID OPENING TIME WILL BE CONSIDERED PROVIDED FORMAL BID AND WRITTEN
ALTERATION HAVE BEEN RECEIVED AND TIME-STAMPED BEFORE BID OPENING TIME. ENTIRE BID SHOULD BE RETURNED, EXCEPT ITEM PAGES NOT
BID.

14. STANDARDS OF QUALITY.

ANY PRODUCT OR SERVICE BID SHALL CONFORM TO ALL APPLICABLE FEDERAL AND STATE LAWS AND REGULATIONS AND THE SPECIFICATIONS CONTAINED IN THE SOLICITATION. UNLESS OTHERWISE SPECIFIED IN THE SOLICITATION, ANY MANUFACTURER'S NAME, TRADE NAME, BRAND NAME, OR CATALOG NUMBER USED IN THE SPECIFICATION IS FOR THE PURPOSE OF DESCRIBING THE STANDARD OF QUALITY, PERFOMANCE, AND CHARACTERISTICS DESIRED AND IS NOT INTENDED TO LIMIT OR RESTRICT COMPETITION. BIDDER MUST SPECIFY THE BRAND AND MODEL NUMBER OF THE PRODUCT OFFERED IN HIS BID. BIDS NOT SPECIFYING BRAND AND MODEL NUMBER SHALL BE CONSIDERED AS OFFERING THE EXACT PRODUCTS SPECIFIED IN THE SOLICITATION.

15. DESCRIPTIVE INFORMATION.

BIDDERS PROPOSING AN EQUIVALENT BRAND OR MODEL SHOULD SUBMIT WITH THE BID INFORMATION (SUCH AS ILLUSTRATIONS, DESCRIPTIVE LITERATURE, TECHNICAL DATA) SUFFICIENT FOR STATE OF LOUISIANA TO EVALUATE QUALITY, SUIT ABILITY, AND COMPLIANCE WITH THE SPECIFICATIONS IN THE SOLICITATION. FAILURE TO SUBMIT DESCRIPTIVE INFORMATION MAY CAUSE BID TO BE REJECTED. ANY CHANGE MADE TO A MANUFACTURER'S PUBLISHED SPECIFICATIONS SUBMITTED FOR A PRODUCT SHALL BE VERIFICABLE BY THE MANUFACTURER. IF ITEM(S) BID DO NOT FULLY COMPLY WITH SPECIFICATIONS (INCLUDING BRAND AND/OR PRODUCT NUMBER), BIDDER MUST STATE IN WHAT RESPECT ITEM(S) DEVIATE. FAILURE TO NOTE EXCEPTIONS ON THE BID FORM WILL NOT RELIEVE THE SUCCESSFUL BIDDER(S) FROM SUPPLYING THE ACTUAL PRODUCTS REQUESTED.

16. BID OPENING.

BIDDERS MAY ATTEND THE BID OPENING, BUT NO INFORMATION OR OPINIONS CONCERNING THE ULTIMATE CONTRACT AWARD WILL BE GIVEN AT THE BID OPENING OR DURING THE EVALUATION PROCESS. BIDS MAY BE EXAMINED WITHIN 72 HOURS AFTER BID OPENING. INFORMATION PERTAINING TO COMPLETED FILES MAY BE SECURED BY VISITING THE STATE OF LOUISIANA DURING NORMAL WORKING HOURS. WRITTEN BID TABULATIONS WILL NOT BE FURNISHED.

17. AWARDS.

THE STATE OF LOUISIANA RESERVES THE RIGHT TO AWARD ITEMS SEPARATELY, GROUPED OR ON AN ALL-OR-NONE BASIS AND TO REJECT ANY OR ALL BIDS AND WAIVE ANY INFORMALITIES.

18. PRICES .

UNLESS OTHERWISE SPECIFIED BY THE STATE OF LOUISIANA IN THE SOLICITATION, BID PRICES MUST BE COMPLETE, INCLUDING TRANSPORTATION PREPAID BY BIDDER TO DESTINATION AND FIRM FOR ACCEPTANCE FOR A MINIMUM OF 30 DAYS. IF ACCEPTED, PRICES MUST BE FIRM FOR THE CONTRACTUAL PERIOD. BIDS OTHER THAN F.O.B. DESTINATION MAY BE REJECTED. PRICES SHOULD BE QUOTED IN THE UNIT (EACH, BOX, CASE, ETC.) AS SPECIFIED IN THE SOLICITATION.

19. DELIVERIES

BIDS MAY BE REJECTED IF THE DELIVERY TIME INDICATED IS LONGER THAN THAT SPECIFIED IN THE SOLICITATION.

20. TAXES.

VENDOR IS RESPONSIBLE FOR INCLUDING ALL APPLICABLE TAXES IN THE BID PRICE. STATE AGENCIES ARE EXEMPT FROM ALL STATE AND LOCAL SALES AND USE TAXES.

STANDARD TERMS & CONDITIONS	INVITATION TO BID	
NUMBER : 2207261 OPEN DATE: 04/27/06 TIME: 04:00 PM T-NUMBER :	BIDDER:	PAGE 3

21. NEW PRODUCTS.

UNLESS SPECIFICALLY CALLED FOR IN THE SOLICITATION, ALL PRODUCTS FOR PURCHASE MUST BE NEW, NEVER PREVIOUSLY USED, AND THE CURRENT MODEL AND/OR PACKAGING. NO REMANUFACTURED, DEMONSTRATOR, USED OR IRREGULAR PRODUCT WILL BE CONSIDERED FOR PURCHASE UNLESS OTHERWISE SPECIFIED IN THE SOLICITATION. THE MANUFACTURER'S STANDARD WARRANTY WILL APPLY UNLESS OTHERWISE SPECIFIED IN THE SOLICITATION.

22. CONTRACT RENEWALS.

UPON AGREEMENT OF THE STATE OF LOUISIANA AGENCY AND THE CONTRACTOR, A TERM CONTRACT MAY BE EXTENDED FOR 2 ADDITIONAL 12-MONTH PERIODS AT THE SAME PRICES, TERMS AND CONDITIONS. IN SUCH CASES, THE TOTAL CONTRACT TERM CANNOT EXCEED 36 MONTHS.

23. CONTRACT CANCELLATION.

THE STATE OF LOUISIANA HAS THE RIGHT TO CANCEL ANY CONTRACT, IN ACCORDANCE WITH PURCHASING RULES AND REGULATIONS, FOR CAUSE, INCLUDING BUT NOT LIMITED TO, THE FOLLOWING: (1) FAILURE TO DELIVER WITHIN THE TIME SPECIFIED IN THE CONTRACT; (2) FAILURE OF THE PRODUCT OR SERVICE TO MEET SPECIFICATIONS, CONFORM TO SAMPLE QUALITY OR TO BE DELIVERED IN GOOD CONDITION;
(3) MISREPRESENTATION BY THE CONTRACTOR; (4) FRAUD, COLLUSION, CONSPIRACY OR OTHER UNLAWFUL MEANS OF OBTAINING ANY CONTRACT WITH THE STATE; (5) CONFLICT OF CONTRACT PROVISIONS WITH CONSTITUTIONAL OR STATUTORY PROVISIONS OF STATE OR FEDERAL LAW;
(6) ANY OTHER BREACH OF CONTRACT.

24. DEFAULT OF CONTRACTOR.

FAILURE TO DELIVER WITHIN THE TIME SPECIFIED IN THE BID WILL CONSTITUTE A DEFAULT AND MAY CAUSE CANCELLATION OF THE CONTRACT.
WHERE THE STATE HAS DETERMINED THE CONTRACTOR TO BE IN DEFAULT, THE STATE RESERVES THE RIGHT TO PURCHASE ANY OR ALL PRODUCTS
OR SERVICES COVERED BY THE CONTRACT ON THE OPEN MARKET AND TO CHARGE THE CONTRACTOR WITH COST IN EXCESS OF THE CONTRACT
PRICE. UNTIL SUCH ASSESSED CHARGES HAVE BEEN PAID, NO SUBSEQUENT BID FROM THE DEFAULTING CONTRACTOR WILL BE CONSIDERED.

25. ORDER OF PRIORITY,

IN THE EVENT THERE IS A CONFLICT BETWEEN THE INSTRUCTIONS TO BIDDERS OR STANDARD CONDITIONS AND THE SPECIAL CONDITIONS, THE SPECIAL CONDITIONS SHALL GOVERN.

26. APPLICABLE LAW.

ALL CONTRACTS SHALL BE CONSTRUED IN ACCORDANCE WITH AND GOVERNED BY THE LAWS OF THE STATE OF LOUISIANA.

27. COMPLIANCE WITH CIVIL RIGHTS LAWS.

BY SUBMITTING AND SIGNING THIS BID, BIDDER AGREES TO ABIDE BY THE REQUIREMENTS OF THE FOLLOWING AS APPLICABLE: TITLE VI AND VII OF THE CIVIL RIGHTS ACT OF 1964, AS AMENDED BY THE EQUAL OPPORTUNITY ACT OF 1972, FEDERAL EXECUTIVE ORDER 11246, FEDERAL REHABILITATION ACT OF 1973, AS AMENDED, THE VETERAN'S READJUSTMENT ASSISTANCE ACT OF 1974, TITLE IX OF THE EDUCATION AMENDMENTS OF 1972, THE AGE ACT OF 1975, AND BIDDER AGREES TO ABIDE BY THE REQUIREMENTS OF THE AMERICANS WITH DISABILITIES ACT OF 1990. BIDDER AGREES NOT TO DISCRIMINATE IN ITS EMPLOYMENT PRACTICES, AND WILL RENDER SERVICES UNDER ANY CONTRACT ENTERED INTO AS A RESULT OF THIS SOLICITATION WITHOUT REGARD TO RACE, COLOR, RELIGION, SEXUAL ORIENTATION, NATIONAL ORIGIN, VETERAN STATUS, POLITICAL AFFILIATION, OR DISABILITIES. ANY ACT OF DISCRIMINATION COMMITTED BY BIDDER, OR FAILURE TO COMPLY WITH THESE STATUTORY OBLIGATIONS WHEN APPLICABLE, SHALL BE GROUNDS FOR TERMINATION OF ANY CONTRACT ENTERED INTO AS A RESULT OF THIS SOLICITATION.

28. SPECIAL ACCOMMODATION.

ANY "QUALIFIED INDIVIDUAL WITH A DISABILITY" AS DEFINED BY THE AMERICANS WITH DISABILITIES ACT WHO HAS SUBMITTED A BID AND DESIRES TO ATTEND THE BID OPENING, MUST NOTIFY THIS OFFICE IN WRITING NOT LATER THAN SEVEN DAYS PRIOR TO THE BID OPENING DATE OF THEIR NEED FOR SPECIAL ACCOMMODATIONS. IF THE REQUEST CANNOT BE REASONABLY PROVIDED, THE INDIVIDUAL WILL BE INFORMED PRIOR TO THE BID OPENING.

29. INDEMNITY.

CONTRACTOR AGREES, UPON RECEIPT OF WRITTEN NOTICE OF A CLAIM OR ACTION, TO DEFEND THE CLAIM OR ACTION, OR TAKE OTHER APPROPRIATE MEASURE, TO INDEMNIFY, AND HOLD HARMLESS, THE STATE, ITS OFFICERS, ITS AGENTS AND ITS EMPLOYEES FROM AND AGAINST ALL CLAIMS AND ACTIONS FOR BODILY INJURY, DEATH OR PROPERTY DAMAGES CAUSED BY THE FAULT OF THE CONTRACTOR, ITS OFFICERS, ITS AGENTS, OR ITS EMPLOYEES. CONTRACTOR IS OBLIGATED TO INDEMNIFY ONLY TO THE EXTENT OF THE FAULT OF THE CONTRACTOR, ITS OFFICERS, ITS AGENTS, OR ITS EMPLOYEES. HOWEVER, THE CONTRACTOR SHALL HAVE NO OBLIGATION AS SET FORTH ABOVE WITH RESPECT TO ANY CLAIM OR ACTION FROM BODILY INJURY, DEATH OR PROPERTY DAMAGES ARISING OUT OF THE FAULT OF THE STATE, ITS OFFICERS, ITS AGENTS OR ITS EMPLOYEES.

30. SIGNATURE AUTHORITY.

IN ACCORDANCE WITH L.R.S. 39:1594 (ACT 121), THE PERSON SIGNING THE BID MUST BE:

- 1. A CURRENT CORPORATE OFFICER, PARTNERSHIP MEMBER OR OTHER INDIVIDUAL SPECIFICALLY AUTHORIZED TO SUBMIT A BID AS REFLECTED IN THE APPROPRIATE RECORDS ON FILE WITH THE SECRETARY OF STATE; OR
- 2. AN INDIVIDUAL AUTHORIZED TO BIND THE VENDOR AS REFLECTED BY A CORPORATE RESOLUTION, CERTIFICATE OR AFFIDAVIT; OR
- 3. OTHER DOCUMENTS INDICATING AUTHORITY WHICH ARE ACCEPTABLE TO THE PUBLIC ENTITY.

SPECIAL TERMS & CONDITIONS	INVITATION TO BID	
NUMBER : 2207261 OPEN DATE: 04/27/06 TIME: 04:00 PM T-NUMBER :	BIDDER:	PAGE 4

1 BID DELIVERY INSTRUCTIONS FOR STATE PURCHASING:

BIDDERS ARE HEREBY ADVISED THAT THE U.S. POSTAL SERVICE DOES NOT MAKE DELIVERIES TO OUR PHYSICAL LOCATION.

BIDS MAY BE MAILED THROUGH THE U.S. POSTAL SERVICE TO OUR BOX AT:
OFFICE OF STATE PURCHASING
P O BOX 94095
BATON ROUGE LA 70804-9095

BIDS MAY BE DELIVERED BY HAND OR COURIER SERVICE TO OUR PHYSICAL LOCATION AS FOLLOWS:

OFFICE OF STATE PURCHASING CLAIBORNE BUILDING, SUITE 2-160 1201 NORTH THIRD STREET BATON ROUGE, LA 70802

BIDDER IS SOLELY RESPONSIBLE FOR ENSURING THAT ITS COURIER SERVICE PROVIDER MAKES INSIDE DELIVERIES TO OUR PHYSICAL LOCATION. THE OFFICE OF STATE PURCHASING IS NOT RESPONSIBLE FOR ANY DELAYS CAUSED BY THE BIDDER'S CHOSEN MEANS OF BID DELIVERY.

BIDDER IS SOLELY RESPONSIBLE FOR THE TIMELY DELIVERY OF ITS BID. FAILURE TO MEET THE BID OPENING DATE & TIME SHALL RESULT IN REJECTION OF THE BID.

**ATTENTION: **

RECEIPT OF A SOLICITATION OR AWARD CANNOT BE RELIED UPON AS AN ASSURANCE OF RECEIVING FUTURE SOLICITATIONS. IN ORDER TO RECEIVE FUTURE SOLICITATIONS/AWARDS FROM THIS OFFICE, YOU MUST ENROLL IN THE PROPER CATEGORY ON LAPAC OR ON STATE PURCHASING'S AGPS BIDDERS LIST. ENROLLMENT IN LAPAC IS FREE AND PROVIDES EMAIL NOTIFICATION OF BID OPPORTUNITIES BASED UPON COMMODITIES THAT YOU SELECT.

2 COMPLIANCE WITH CIVIL RIGHTS LAWS. BY SUBMITTING AND SIGNING THIS SOLICITATION, THE BIDDER AGREES TO ABIDE BY THE REQUIREMENTS OF THE FOLLOWING AS APPLICABLE: TITLE VI AND TITLE VII OF THE CIVIL RIGHTS ACT OF 1964, AS AMENDED BY THE EQUAL OPPORTUNITY ACT OF 1972, FEDERAL EXECUTIVE ORDER 11246, THE FEDERAL REHABILITATION ACT OF 1973, AS AMENDED, THE VIETNAM ERA VETERAN'S READJUSTMENT ASSISTANCE ACT OF 1974, TITLE IX OF THE EDUCATION AMENDMENTS OF 1972, THE AGE ACT OF 1975, AND BIDDER AGREES TO ABIDE BY THE REQUIREMENTS OF THE AMERICANS WITH DISABILITIES ACT OF 1990. BIDDER AGREES NOT TO DISCRIMINATE IN ITS EMPLOYMENT PRACTICES, AND WILL RENDER SERVICES UNDER ANY CONTRACT ENTERED INTO AS A RESULT OF THIS SOLICITATION, WITHOUT REGARD TO RACE,

SPECIAL T	ERMS & C	ONDI	TIONS	INVITATION TO BID	
NUMBER : 220 OPEN DATE: 04/ T-NUMBER :	07261 27/06	TIME:	04:00 PM	BIDDER:	PAGE 5
	STATUS, DISCRIMI STATUTOR	POLI NATI Y OB ION	TICAL AFFILE ON COMMITTED LIGATIONS WI OF ANY CONTR	EXUAL ORIENTATION, NATIONAL ORIGIN, VETERAN NATION, OR DISABILITIES. ANY ACT OF D BY BIDDER, OR FAILURE TO COMPLY WITH THESE HEN APPLICABLE, SHALL BE GROUNDS FOR RACT ENTERED INTO AS A RESULT OF THIS	
3	A PREFER	RENCE	MAY BE ALL	NCE WITH LOUISIANA REVISED STATUTES 39:1595, OWED FOR PRODUCTS MANUFACTURED, PRODUCED, LOUISIANA OF EQUAL QUALITY.	
	DO YOU O	CLAIM	THIS PREFE	RENCE? YES	
	SPECIFY	LINE	NUMBER(S):	· · · · · · · · · · · · · · · · · · ·	
				LOUISIANA WHERE THIS PRODUCT IS MANUFACTURED,	
	(NOTE:	TF	MORE SPACE T	S REQUIRED, INCLUDE ON SEPARATE SHEET.)	
				BUSINESS WORKFORCE? YES NO	
	IF SO,	DO Y	OU CERTIFY T	HAT AT LEAST FIFTY PERCENT (50%) OF YOUR FORCE IS COMPRISED OF LOUISIANA RESIDENTS?	
	YES	_	NO		
				E INFORMATION MAY CAUSE ELIMINATION FROM ES SHALL NOT APPLY TO SERVICE CONTRACTS.	
4		TE O		RESERVES THE RIGHT TO CANCEL THIS CONTRACT WITH NOTICE.	
	BRAND N THE ITE	AME . M DE IEVE	AND/OR PRODU VIATES. FAI	LY COMPLY WITH SPECIFICATIONS (INCLUDING JCT NUMBER), BIDDER MUST STATE IN WHAT RESPECT LURE TO NOTE EXCEPTIONS ON THE BID FORM WILL SFUL BIDDER FROM SUPPLYING THE ACTUAL PRODUCT	
6	ENCLOSE	D WI	TH THE BID	SPECIFIED, SUFFICIENT INFORMATION SHOULD BE IN ORDER TO DETERMINE QUALITY, SUITABILITY, AND ECIFICATIONS.	
	FAILURE CONSIDE			THIS REQUEST MAY ELIMINATE YOUR BID FROM	
				•	

SCOPE OF CONTRACT

SUBMITTAL OF ANY TERMS AND CONDITIONS CONTRARY TO THOSE OF THE STATE OF LOUISIANA MAY CAUSE YOUR BID TO BE REJECTED. BY SIGNING BELOW,

SPECIAL TERMS & CONDITIONS	INVITATION TO BID	
NUMBER : 2207261 OPEN DATE: 04/27/06 TIME: 04:00 PM T-NUMBER :	BIDDER:	PAGE 6

TERMS AND CONDITIONS WHICH MAY BE INCLUDED IN YOUR BID ARE NULLIFIED, AND CONTRACTOR AGREES THAT THIS CONTRACT SHALL BE CONSTRUED IN ACCORDANCE WITH AND GOVERNED BY THE LAWS OF THE STATE OF LOUISIANA.

BIDDER SIGNATURE

RICE SI	2207261	INVITATI	ON TO BI) 	
PEN DATE :	04/27/06 TIME: 04:00 PM	BIDDER:			PAG
LINE NO.	COMMODITY/SERVICE DESCRIPTION	QUANTITY FROM/TO	UNIT	UNIT PRICE	EXTENDED TOTAL
<u>-</u>	UNLESS SPECIFIED ELSEWHERE SHIP TO: PUBLIC SAFETY SERVICES OFFICE OF STATE POLICE RADIO COMMUNICATION PARTS 8001 INDEPENDENCE BLVD BATON ROUGE, LA 70806			•	
00001	COMMODITY CODE: 070-59-000000	1	EACH		
	MOBILE EMERGENCY COMMUNICATIONS TOWER TRAILER WITH 100 FT TOWER, SHELTER, AND GENERATOR.				
	SEE ATTACHED SPECIFICATIONS.				
	SPECIFY BRAND (& NUMBER IF APPLICABLE)				

Department of Public Safety Purchase Description and Salient Characteristics of

Mobile Tower Trailer

Scope: This requirement is for a commercial, bi-axle trailer with a minimal 100 foot heavy duty telescoping tower, air conditioned equipment shelter and additional accessories. This trailer combination shall comply with applicable Federal and State Department of Transportation Motor Carrier Safety Regulations, Motor Vehicle Safety Standards, Society of Automotive Engineering Standards, commercial workmanship, materials and construction practices common in the industry. The tower shall also comply with industry regulations governing its safe use and application. This trailer configuration shall be capable of being licensed for travel anywhere in the United States for use on paved roads.

General: The trailer and load will be balanced capable of safety supporting and traveling with the tower, stored equipment, shelter, 2000 pounds additional equipment, spare tire and storage box for a guy/anchor set and miscellaneous tools.

Trailer

Trailer Decking: Decking covering the upper surface of the trailer, with non-skid surface. Intended use is to support personnel during system configuration/operation.

Leveling Jacks: The trailer shall have self-contained leveling jacks. Four jacks are required, one on each corner which will allow the trailer to be leveled in uneven terrain on slopes up to and including 5 degrees. The leveling jacks shall be storable for transport such that they do not impede movement or turning.

Trailer Type: Trailer shall be bi-axle flatbed with load range "G" tires and wheels.

Trailer Brake: The trailer shall have the appropriately rated electric actuating drum brakes. The brakes shall comply with the performance requirements specified in the Department of Transportation Federal Motor Carrier Safety Regulations, section 393.52. The electric trailer brake system should have a standard break-away switch which will engage the brakes in the event of the trailer separating from the tow vehicle. Break-away system shall include a battery w/battery box and provide a means of charging while the trailer is in tow.

Trailer Frame Construction: Chassis frame shall be the manufacturer's current standard all-steel construction hot dip galvanized having structural capacity to withstand the flexural and torsional forces, without permanent set or part failure under normal operating conditions.

Tongue: The tongue shall be the manufacturer's current standard all-steel construction and shall provide structural strength to resist bending and twisting without permanent deformation or damage under normal operating conditions. The tongue shall conform to applicable requirements of the Department of Transportation Federal Motor Carrier Safety Regulations. The tongue shall be fitted with a platform that will accept the mounting of an Auto Acquisition VSAT (weight: 300lbs, Mounting footprint: W 48" X D 84").

Suspension: Trailer shall be equipped with manufacturer's standard suspension system with components have rated capacity at least equal to the load imposed on each member, measured at the ground, with the

trailer loaded with the maximum payload. The bi-axle suspension system shall have leaf springs and two one-piece through shafts.

Axles: The axles shall be the manufacturer's current standard for the trailer specified. Axle rating shall be at least equal to the load imposed on each axle, measured at the ground, with the trailer loaded to gross weight. The axle system shall provide sufficient articulation to maintain equal loading on each wheel.

Wheels & Rims: Wheels shall be the manufacturer's current standard. The trailer shall be furnished with four dual wheels.

Tires: Tires shall be tubeless type with highway tread. Tires shall be rated capacity at least equal to the load imposed on each tire measured at the wheel, at the ground, with trailer loaded with its maximum rated payload, (Load Range "G").

Spare Tire: The trailer shall be outfitted with a spare tire and wheel. The spare tire and wheel shall be mounted on trailer and secured with a lock. Tire shall be tubeless type with highway tread. Tire shall be rated capacity at least equal to the load imposed on each tire measured at the wheel, at the ground, with trailer loaded with its maximum rated payload, (Load Range "G").

Safety Chains: Safety chains, conforming to the requirement of Department of Transportation Federal Motor Carrier Safety Regulations, and SAE J697, shall be furnished.

Lighting & Wiring System: Lighting and wiring system shall be manufacturer's standard of 12 volt potential negative ground and shall comply with DOT Federal Motor Carrier Safety Regulations. Wiring pattern, wire color code, coupling connector socket, and installation shall conform to SAE J560. Lights and reflectors shall be recessed and guarded, and wiring shall be properly routed and anchored for protection from damage. Turn signal lamps shall comply with SAE J588, Class A. A seven conductor RV type mating connector shall be provided.

Tongue Jack: A full retractable tongue jack shall be provided.

Trailer Tool Kit: A tool kit will be supplied for trailer and tower set up, minor repairs, and adjustment.

Storage Box: An aluminum storage box with built in lock shall be provided and capable of storing the guy and anchor kit, lug wrench, jack and miscellaneous tools. The box shall be located on trailer frame. Box should be weatherproof to prevent water leakage from normal and wind driven rainfall. (Such as when traveling on highways at speeds of 70 MPH)

Coaxial Cable Reel: A free-spinning reel capable of winding and stowing 300' of 5/8" cable, or its equivalent, (not to include the cable) shall be provided.

Work Lights: One 12V DC work light mounted on the trailer to light the tower control box. One 12V DC work light mounted to the trailer to light the generator controls. Lights should work off of power from the tow vehicle.

SHELTER

Dimension: The shelter should be approximately 96 inches (8 ft) by 168 inches (14 feet) by 93 inches high (7 feet, 9 inches). All shelter dimensions are outside dimensions.

Walls: The walls shall be approximately 2 inches thick, constructed from commercial grade studs spaced approximately 12 inches apart and include one inch thick foam insulation offering an insulation factor of R-

20 or greater. The outer surface shall be skinned with steel/aluminum and the inner walls shall be covered with a commercial wallboard.

Floor: The floor shall be sufficiently rigid, aluminum diamond plate and an aluminum structure supporting it, capable of supporting 300 pound/square foot equipment load.

Door: The door shall be heavy duty with heavy-duty hardware, and capable of locking. The doors shall be 36 inches wide. The door shall be on the curbside with the hinge side forward.

Roof & Frame: The roof and frame of the shelter shall be capable of supporting collapsed tower in horizontal stowed position for being trailered and capable of supporting 300 pound/square foot.

Ladder: A ladder attached to the shelter shall provide roof access.

I/O Ports: Three standard 2" hole tubular input/output ports shall be included through rear wall for easy routing of the antenna cables and one for miscellaneous data lines. A rain guard should be placed above the ports so as to prevent water from entering shelter.

Water Leakage: The shelter shall be adequately sealed (including door) to prevent water leakage from normal and wind driven rainfall. (Such as when traveling on highways at speeds of 70 MPH)

Air Conditioner & Heat Unit: The 2 ton air conditioner/heat (2) units shall be of a mobile shelter type, with a cooling capacity of at least 22,500 BTUs each and will include heat strips, suitable for mobile shelter applications such as being capable of travel over specified roads without failures. These will be mounted on the rear wall on each side of the transfer switch.

Electrical: All wiring shall be run through approved conduit attached to the walls. Electrical requirements shall conform to applicable regulations and standards. The shelter shall be wired for 240VAC, 200 AMP, single-phase power, and complete with the following equipment:

- A manual transfer switch to transfer the load from shore power to the generator (mounted in the center of the rear wall).
- Wiring from transfer switch will be terminated in a 200 amp power circuit breaker panel with no less than one main and 42 breakers. Panel will be mounted on the door side wall.
- Three Quad outlets on both side walls (16 inches from the floor and evenly spaced). Each outlet will be on its own circuit.
- Two four feet fluorescent lights (one each side of center running back to front).
- Two Quad outlets mounted externally on the rear wall (two feet above bottom of the shelter). These outlets should have weatherproof enclosure and should be on individual circuits.
- Two outlets should be mounted at mid-level on the rear wall to accept plugs for air conditioner units. These plugs should be 20 amp and on individual circuits.
- · Light switch should be next to the door.

TOWER

General: Heavy duty, telescoping tower supplied with necessary outriggers, guy-anchor set, power winch and backup hand cranking mechanism to extend and retract the tower. The retracted tower shall be stowed in a horizontal position with the top facing toward the trailer hitch over roof of the shelter for transporting. An operator shall easily be able to tilt the top of the retracted tower from its horizontal stowed position to a vertical position located at the rear of the shelter and trailer.

Height: The tower shall be approximately 100 feet extended with the mast and not to exceed 27 feet retracted with mast removed.

Mast & Rotor: The tower top section shall be capable of accepting a rotor. Two rotors will be provided: One to support two masts (one mast each side), and one to support three masts evenly spaced. Three masts will be provided. A rack for all mast will be attached to the trailer to be used in transport.

Crank-Up Mechanism: A electric hoist system shall be provided. The hoist shall be industry approved for this application. Hoist shall also have manual operated hand crank.

Stowed: Stowed position of tower shall be in horizontal position in line with trailer on top of the shelter. Additional stabilizing and support members will be provided to safely secure tower to shelter-trailer. i.e. Tie-down straps.

Guys & Anchors: A complete temporary guy and anchor set shall be provided. When guyed the tower should withstand 95 MPH winds.

Guy and Ground Anchor Tool Kit: A tool kit will be supplied to aid in installation of guy and ground anchors. (if applicable)

Grounding Kit: A grounding kit capable of attaching to the tower and providing a ground shall be supplied.

Generator: A 15 KW diesel fueled generator will be supplied with a double walled fuel tank with a capacity of 55 gallons. The fuel tank will have a gauge that will have markings of at least "full, half, and empty" for fuel level. The generator will have an onboard battery charger with a male plug (weatherproof enclosure) that can be connected by a common extension cord to any AC wall outlet. The generator will have a master Battery Disconnect switch. The generator shall be of commercial or industrial quality and manufactured by a reputable company.

Manual Transfer Switch: A method of switching from the generator to an outside power source shall be supplied. This transfer switch shall be rated to carry the load of the generator.

Shore Power Connection: A 100 Amp external connector shall be supplied for electric power when the generator is not in use.

Shelter Finish: The shelter shall be painted gloss white with a transportation grade paint system.

WORKMANSHIP & DOCUMENTATION

Workmanship: Metal fabrication: The metal used in fabrication shall be free from kinks, harp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the metal to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means uo insure uniformity of size and shape.

Documentation: The supplier shall provide specification sheet, operating instructions and safety guidelines for overall usage of tower and trailer system.